MSBH

STH for reflow soldering

MSL1



Last release

Your drawings and notes

General data

Dimensional class:	low
Standard colour:	black
Pitches:	metric 5 mm, 10 mm (.197 in, .394 in) imperial 5.08 mm, 10.16 mm (.200 in, .400 in)
Screw dimension:	M3
Recommended/highest tightening torque:	0.5/0.6 Nm (4.42/5.31 lbf·in)
PCB thickness:	max. 2.4 mm (.094 in)
PCB hole diameter:	1.3 mm (.051 in)
Stripping length	5 ÷ 6 mm (.197 ÷ .24 in)
Operating temperature range	-40 °C ÷ +105 °C (-40 °F ÷ +221 °F)
Contact resistance	<15 mΩ
Insulating material group:	I (CTI ≥ 600V)
Self-extinguishing class UL94:	V0
Insulation resistance	>10^9 Ω (500V DC)

Certifications

UL (n. E167473)
300 V - 13.5 A (*), 10 A (**) - 30÷16 AWG - for 5 mm, 5.08 mm pitch
600 V - 13.5 A (*), 10 A (**) - 30÷16 AWG - for 10 mm and 10.16 mm pitch
*factory wiring - **field wiring

Data according to

IEC EN 60947-7-4
250 V - 17.5 A - 1.5 mm² solid (13.5 A - 1 mm² stranded) for 5 mm and 5.08 mm pitch
750 V - 17.5 A - 1.5 mm² solid (13.5 A - 1 mm² stranded) for 10 mm and 10.16 mm pitch

Application values for end-use equipment have to be in accordance to norms and applicable to it. The certifications of some product's versions could be pending, for more detailed and updated data please refer to our web site **www.sauro.net** or your representative Sales Manager.

A higher number of poles is obtained by combining together **modular** parts.



0°, side stackable
MSBH__001-0N 2 ÷ 12 poles, 5 mm .197" pitch
MSBH__002-0N 2 ÷ 6 poles, 10 mm .394" pitch
MSBH__005-0N 2 ÷ 5 poles, 5.08 mm/.200" pitch
MSBH__006-0N 2 ÷ 3 poles, 10.16 mm/.400" pitch



55°, modular
MSBH__045-0N 2÷16 poles, 5.08 mm / .200" pitch
MSBH__046-0N 1÷8 poles, 10.16 mm / .400" pitch



55°, side stackable
MSBH__061-0N 2÷5 poles, 5 mm / .197" pitch
MSBH__062-0N 2÷3 poles, 10 mm / .394" pitch
MSBH__065-0N 2÷16 poles, 5.08 mm / .200" pitch
MSBH__066-0N 2÷8 poles, 10.16 mm / .400" pitch



90° terminal aligned with cable entry, modular
MSBH__T01-0N 2÷25 poles, 5 mm / .197" pitch
MSBH__T02-0N 1÷13 poles, 10 mm / .394" pitch
MSBH__T05-0N 2÷8 poles, 5.08 mm / .200" pitch
MSBH__T06-0N 1÷4 poles, 10.16 mm / .400" pitch





90° terminal aligned with cable entry, side stackable
MSBH__TA1-0N 2÷25 poles, 5 mm / .197" pitch
MSBH__TA2-0N 2÷13 poles, 10 mm / .394" pitch
MSBH__TA5-0N 2÷8 poles, 5.08 mm / .200" pitch
MSBH__TA6-0N 2÷4 poles, 10.16 mm / .400" pitch